

Dry Lining Paint

DESCRIPTION

Johnstone's Dry Lining is a high quality flat matt emulsion specially formulated for application onto bare or primed/sealed Dry Lining boards. It's enhanced opacity and flat matt finish significantly reduces the appearance of surface imperfections in areas featuring critical lighting. It offers excellent coverage and application qualities with a drying time of 1-2 hours making the job easier to complete.

RECOMMENDED USES



Ceiling & walls.

TYPE OF SUBSTRATE

Suitable for use on plasterboard/wallboards/dry lining boards.

COLOUR RANGE

Available in over 6,000 colours via the Johnstone's CMS 2010 Tinting System.

FINISH

Matt

VOLUME SOLID

27%

COVERAGE



Johnstone's Dry Lining will cover approximately 12-14 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC Content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010)
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 90µm Dry: 24µm

KEY PROPERTIES

- For use on bare or primed / sealed Dry Lining boards
- Hides surface imperfections highlighted by critical lighting
- Easy to touch up
- Touch dry in 1-2 hours

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. For additional information and free Johnstone's Trade datasheets call 01924 354000 or visit www.johnstonestrade.com.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal new/bare surfaces with a coat of Dry Lining thinned up to 10% with clean water. Finish with two full coats of Dry Lining paint. Do not apply in temperatures below 10°C.

Plasterboards which have been initially coated with the board manufacturers specified primer/ sealer should also be finish with two coats of Dry Lining paint.

CLEANING / AFTER USE



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

10 Litre.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.