

4.7

Heavy Duty Glaze

DESCRIPTION

A tough, water-borne durable gloss coating for added protection in high traffic areas. Suitable for application over most interior decorative coatings.

RECOMMENDED USES



For added protection of interior wall surfaces subject to heavy traffic. Especially suitable as a protective coating.

SPECIAL PROPERTIES

Tough, durable coating.

COLOUR RANGE

Clear

FINISH

Gloss.

VOLUME SOLID

29%.

COVERAGE



Johnstone's Heavy Duty Glaze will cover at the rate of approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 2 hours.
Recoat after approximately 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/b): 150g/l (2007) / 100g/l (2010).
This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 83µm, dry: 25µm.

SIZE

5 Litre

PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease. For further advice contact Technical Advisory on 01924 354100.

APPLICATION



Stir well before use. Suitable for application by brush, spray or mohair roller. Apply a single coat of uniform thickness, taking care to avoid runs or overlapping. Do not apply when air or surface temperature is below 5°C, or in humid conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT.
- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.



SigmaKalon DECORATIVE COATINGS UK AND IRELAND, SIGMAKALON UK LIMITED

Huddersfield Road, Birstall, Batley, West Yorkshire WF17 9XA Telephone: 01924 354000 Facsimile: 01924 354001 www.johnstones-paints.co.uk