

DESCRIPTION

Satin Woodstain has been specially formulated for smooth timber joinery such as doors, windows, fascia boards, cladding and garden furniture to provide a microporous satin finish that highlights the natural grain of the wood. It is especially beneficial when used on exterior joinery (hardwood or softwood) but can also be used on interior wood.

AVAILABLE IN

750ml, 2.5 litre and 5 litre sizes.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPES OF SUBSTRATE

Doors, window frames, fascia boards, cladding, garden furniture.

COVERAGE



Approximately 15 square metres per litre depending on the nature and porosity of the surface being stained.

DRYING TIME



Touch dry in 3-6 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/e): 500g/l (2007).
This product contains max 500g/l VOC.

PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any resins and natural oils using White Spirit. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Previously untreated softwood should be treated with a suitable clear preserver. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Satin Woodstain thoroughly before use. Apply two or more coats of varnish evenly, by brush along the wood grain as required, paying particular attention to the end grain. On bare or new wood, apply at least two coats of Satin Woodstain to give maximum durability. A third coat may be required where extreme weather conditions exist. **PLEASE NOTE:** The final colour will depend on the original colour of the wood and the number of coats applied.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT PRODUCT.
- FLAMMABLE.
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- In case of insufficient ventilation wear suitable respiratory protective equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- Keep out of the reach of children.



PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.