

DESCRIPTION

Yacht Varnish has been specially formulated for use on all exterior smooth planed timber, doors and window frames. A traditional marine quality varnish, it provides a flexible varnish film that flexes with the timber surface.

AVAILABLE IN

750ml, 2.5 litre and 5 litre sizes.

COLOUR RANGE

Clear Gloss.

RECOMMENDED USES




Suitable for exterior use.

TYPES OF SUBSTRATE

Doors, window frames and all smooth planed exterior timber.

COVERAGE



Approximately 15 square metres per litre depending on the nature and porosity of the surface being varnished.

DRYING TIME



Touch dry in 2–4 hours.
Recoat after 16–24 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.
STORE AWAY FROM HEAT AND FLAME.

CLEANER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
EU limit value for this product (Cat A/e): 500g/l (2007) / 400g/l (2010).
This product contains max 400g/l VOC.

PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Previously untreated softwood should be coated with a suitable clear preserver. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Yacht Varnish thoroughly before use. Apply two or more coats of varnish evenly, by good quality brush along the wood grain as required paying particular attention to the end grain. Do not overlap the brush strokes.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean brushes immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **FLAMMABLE.**
- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- If swallowed, seek medical advice immediately and show this container or label.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – **DO NOT USE SOLVENT OR THINNERS.**
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

