

DESCRIPTION

Woodworks Teak Oil penetrates timber, replacing the lost natural oils and enhances the natural beauty of the wood. With a low sheen finish, it is ideal for the upkeep of exterior hardwood.

AVAILABLE IN

500ml

RECOMMENDED USES



Suitable for interior & exterior use.

TYPES OF SUBSTRATE

Interior and exterior bare timber with knots, doors, door frames, furniture and railings.

COVERAGE



Woodworks Teak Oil will cover approximately 15-20sqm per litre, depending on the nature and porosity of the timber.

DRYING TIME



Product will be dry / recoatable after 12 hours at room temperature.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION.

CLEANER

Methylated Spirit.

VOC CONTENT

HIGH VOC CONTENT 25-50%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

PREPARATION

Ensure that the wood to be treated is thoroughly clean, dry, and free from resinous matter or loose particles. Clean oily timber with White Spirit. Rub down the surface with abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Apply Woodworks Teak Oil liberally by using a cloth or brush. Remove excess Linseed Oil after 10-15 minutes with a clean cloth. Up to 3 coats may be required for bare timber, rubbing previous coat with fine sandpaper for a key; use 1 coat for maintenance of existing coating.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Flammable liquid and vapour.
- May be fatal if swallowed and enters airways.
- Hazardous ingredients: Naphtha (petroleum) hydrotreated heavy:Nota(s) P
- Safety data sheet available on request.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting.
- Store in a well-ventilated place. Keep cool.
- Store locked up.