

Fast Drying Water Based Undercoat

Leyland Fast Drying Undercoat has been specially developed to work with Leyland Trade Fast Drying High Gloss. A quick drying, high performance undercoat for interior and exterior suitably primed metal and a combined primer and undercoat for interior and exterior wood. The non yellowing formula benefits from excellent flow and is both fast drying and low odour ensuring easy application and minimal downtime.

Recommended uses

Interior ✓ Exterior ✓

Type of substrate

Wood and primed metal. For further advice on other substrates contact Technical Advisory.

Colour availability

Brilliant White, Dark Grey and thousands of additional colours are available via the Leyland tinting system.

Finish

N/A

Volume solid

36%

Coverage

1 litre will cover approximately 13 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats.

Drying time

Recoat after 1-2 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

VOC content

LOW VOC CONTENT 0.3-7.99%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130 g/l (2010). This product contains max 15 g/l

Film thickness

Wet: 77µm
Dry: 27µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down bare timber surfaces with fine waterproof abrasive paper to remove raised grain and sharp edges. Apply Knotting Solution to knots and resinous surfaces. Rub down sound previously gloss painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime where required with the appropriate Leyland Primer. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Allow radiators to cool before painting.

Application

Stir well before use. Apply by brush or roller. Apply liberally, brushing firmly into the surface. Treat all accessible timber, in particular the end grain. Allow 1-2 hours before applying a second coat if required. Conditions of low temperature or high humidity can prolong the drying time. Do not apply when air or surface temperature is below 10°C or externally when rain is imminent.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.